




ORAFLEX® Cushion Mounting Tapes

The **ORAFLEX**® Cushion Mounting Tapes are manufactured with modern acrylic pressure sensitive adhesives and are based on the latest product designs. The specially developed adhesive compounds offer different levels of tack and repositionability. **ORAFLEX**® Cushion Mounting Tapes are resistant to the solvents used in the flexographic printing industry.

ORAFLEX® Cushion Tapes Construction



Quality for a reliable printing process

The **ORAFLEX®** Cushion Mounting Tapes guarantee the highest quality for the entire printing process.

The design of the **ORAFLEX®** Cushion Mounting Tapes ensures optimal handling and increased reusability due to the special construction.

The high quality of the foam ensures perfect damping / absorption of vibrations during the printing process. The 0.38 mm thick adhesive tapes have a high tolerance to pressure changes and allow a fast and optimal adjustment of the pressure supply.


The medium-hard **ORAFLEX**® Cushion Mounting Tapes (1175X) offer a wide range of linear dot gain. This simplifies the selection for tape hardness - a medium-hard plate mounting tape is suitable for most combinations and printing requirements.

ORAFLEX® Cushion Mounting Tapes ensure outstanding printing results.




Product overview

ORAFLEX® Cushion product code identification



Choose the right adhesion level



ORAFLEX® Solid


The **ORAFLEX®** Solid tapes are a range of double-sided hard tapes for photopolymer or rubber plate mounting on print cylinders for flexography, letterpress and label printing. **ORAFLEX®** Solid products are designed with balanced adhesion levels to give good plate security while allowing distortion-free repositioning and demounting. The adhesives are designed to remove clearly and without residues from sleeves and metal cylinders after use.

Product characteristics

| | ORAFLEX® 11395 | ORAFLEX® 11396 | ORAFLEX® 11397 |
|-------------------------|---|------------------------------|------------------------------|
| Thickness without Liner | 100 micron 4 mil | 200 micron 8 mil | 300 micron 12 mil |
| Liner colour | | | |
| Adhesive | Natural rubber | Natural rubber | Natural rubber |
| Liner | PP filmic Brown Creped | PP filmic White Creped | PP filmic Green Creped |
| Carrier | PET film transparent | PP film transparent | PP film transparent |
| Roll sizes | 310 mm x 25 m, 620 mm x 25 m, 900 mm x 25 m, 1200 mm x 25 m, 1250 mm x 25 m | | |




Application guide





ORAFOL's Worldwide Locations









ORAFOL Europe GmbHOrafolstraße 1, D-16515 Oranienburg, Germany

Tel: +49 (0)3301 864-0 / adhesive.tapes@orafol.de

Find out more about our products at: www.orafol.com · www.orafoleurope.com

